


Health	1
Flammability	2
Reactivity	1
PPI	G

MATERIAL SAFETY DATA SHEET

WILD - AEROSOL



HMIS SYMBOL

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

Product Name: **WILD - Aerosol**
 Chemical Family: Mixture
 Use: Wire Line Dressing, Lubricant, Penetrant, Coating, Cleaner, and Corrosion Inhibitor.

Manufacturer/Supplier: Preferred Industrial
 3160-21331 Gordon Way
 Richmond, BC Canada V6W 1J9
 Phone: (604) 231-6030 Fax: (604) 247-1610
 Toll Free: 1-866-522-1600

Emergency:
 CANUTEC PH: (613) 996-6666 Cell: *666 TTY/TDD: 1-888-675-6863

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components	Hydrotreated Kerosene	Propellant
CAS NO.	64742-47-8	124-38-9
WT %	40 - 70	1 - 5
OSHA PEL	Not Established	5000mg/L
ACGIH TLV	200mg/m ³	5000mg/L
LD50	Not Determined	Not Determined
LC50	Not Determined	Not Determined
OTHER:	N/A	N/A

SECTION 3 - HAZARDS IDENTIFICATION

Route of Entry: Eyes, Inhalation, Ingestion, Skin
 Eyes: May cause irritation to eyes.
 Inhalation: Viscous nature may block breathing passages if inhaled.
 Ingestion: May cause diarrhea if ingested.
 Skin: May cause irritation after prolonged skin exposure, especially for persons with hyper sensitivity.

SECTION 4 - FIRST AID MEASURES

Eyes: Flush with water until all residual material is gone. If irritation persists, seek medical help.
 Ingestion: Do not induce vomiting. Wash out mouth. Contact a physician immediately.
 Skin: Remove by wiping or with a waterless hand cleaner, followed by washing with soap and water.
 Inhalation: Clear air passage. If breathing difficulty continues seek medical help.

SECTION 5 - FIRE FIGHTING MEASURES

Flammability: Nil at ambient temp
 Extinguishing Media: Use dry chemicals, foam, halon, CO₂
 Flash Point (COC): 79°C (174°F)
 Explosive Properties: LEL - 1.5% UEL - <10.5%
 Autoignition Temp: 229°C (444°F)
 Hazardous Combustion Products: Oxides of carbon, smoke and irritating vapors as products of incomplete combustion.
 Protective Equipment: Self-contained breathing apparatus.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Spillage: Scoop up excess, then wipes down the affected area and pick up residue with diatomaceous earth to avoid a walking hazard.
 Environmental Precautions: Do not allow product to enter into drains.

SECTION 7 - HANDLING AND STORAGE

Handling Procedures: No special handling precautions necessary. Do not pressurize, cut, heat or weld empty containers.
 Storage Requirements: Store in a cool, well ventilated place.
 Engineering Controls: If user's operation generates vapors or mists, use ventilation to keep exposure to airborne contaminants below the exposure limit. Make up air should always be supplied to balance air removed by exhaust ventilation. Ensure eyewash station and safety shower are close to work station.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Personal Protective Equipment (PPE's):
 Respiratory Protection: Breathing apparatus in confined space areas.
 Hand Protection: Protective gloves for hypersensitive persons.
 Eye Protection: Protective glasses if applied to moving parts.
 Body Protection: Protective overalls.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Aerosol Odor: Solvent
 Odor Threshold: Not Determined Specific Gravity, Typical: 0.83
 Vapor Pressure: <0.01 kPa Vapor Density: >5
 Boiling Point: >149°C (300°F) Melting Point: -40°C (-40°F)
 pH: Neutral Water Solubility: Nil
 Density, Typical: 0.83 g/cm³ Volatile %: Not Determined
 Evaporation Rate (Butyl Acetate = 1.0): <0.01

SECTION 10 - STABILITY AND REACTIVITY

Stability: Chemically stable under normal conditions. No photoreactive agents.
 Conditions to Avoid: Powerful sources of ignition and extreme temperatures.
 Materials to Avoid: Strong acids and oxidizing agents.
 Hazardous Decomposition Products: May release CO_x, smoke and irritating vapors when heated to decomposition.

SECTION 11 - TOXICOLOGICAL INFORMATION

Exposure Limit of Material: See Section 2
 LC50 of Ingredients, Species and Routes: See Section 2
 LD50 of Ingredients, Species and Routes: See Section 2
 Teratogenicity, Embryotoxicity and/or Fetotoxicity: Not Available
 Mutagenicity: Not Available
 Effects of Long-Term (Chronic) Exposure: Long term dermal application may produce possible skin irritation. Elevated temperatures or mechanical action may form vapors or fumes. Inhalation of oil mists or vapors may cause irritation of the upper respiratory tract.
 Carcinogen: NTP: No IARC: No OSHA: No

SECTION 12 - ECOLOGICAL INFORMATION

Possible Effects: May generate oil fractions that could act as a marine pollutant, but is highly unlikely.
 Behavior: Relatively well behaved. Bioaccumulation potential almost nil.
 Environmental Fate: Product will float and spread across water making it a nuisance contaminant.

SECTION 13 - DISPOSAL CONSIDERATIONS

Consult federal, provincial and local regulations for disposal of aerosol products. Do not incinerate.

SECTION 14 - TRANSPORT INFORMATION

TDG (Canada): The mixture is not specifically listed in the Canadian Transportation of Dangerous Goods regulations. The mixture is not regulated.
 Shipping Name: AEROSOLS, Flammable
 UN No.: UN1950
 Packing Group: III
 Classification: CLASS 2.1, Flammable Aerosols
 Labeling Requirements: Limited Quantity labels for containment less than LQI of 6 L net contents per containment. Class 2.1 Label if > 6 L net contents per containment or large containment.
 Placard Requirements: Limited Quantities - None required. Large Containment - Class 2.1

SECTION 15 - REGULATORY INFORMATION

WHMIS: A, B-5, D-2b
 DSL: All components listed
 CPR Compliance: This product has been classified in accordance with the hazard criteria of the Controlled Product Regulations and the MSDS contains all of the information required by those regulations.

SECTION 16 - OTHER INFORMATION

CPR - Controlled Product Regulations
 DSL - Domestic Substance List

As of issue date, the information contained herein is accurate and reliable to the best of Preferred Industrial's knowledge. Preferred Industrial does not warrant or guarantee its accuracy or reliability and shall not be liable for any loss or damage arising out of the use thereof. It is the users' responsibility to be satisfied that the information offered for their consideration is suitable for their particular use.

Prepared by: Preferred Industrial
 Last Date of Revision: November 16, 2012